Manual Multi

SPECIFICATION

MODEL	0640TF	2050FF	3565FF
TYPE	TOP MOUNT	SIDE MOUNT	SIDE MOUNT
FLOW RATE	6m³/hr	20m³/hr	35m³/hr
INLET/ OUTLET/ DRAIN CONNECTION	1.5"	2"	2.5"
MAX.OP. PRESSURE	5kg/cm2	5kg/cm2	5kg/cm2
EJECTOR SUCTION @2kg/cm³	750 LPH	1000 LPH	2500 LPH
EJECTOR RATIO	1:1	1:1	1:1

FEATURES

- Pressure Gauge Adaptor at Inlet (25 NB & 40 NB)
- True Union joint for Disconnection
- Drain elbow with Union

Super Quality Multiport Valves

port Valve

SPECIFICATION

MODEL	MPV0225TF	MPV0525FF	MPV1240FF
TYPE	TOP MOUNT	TOP MOUNT	SIDE MOUNT
FLOW RATE	$3m^3/hr$	$5m^3/hr$	$12m^3/hr$
INLET/ OUTLET/ DRAIN CONNECTION	1" (3/4 Optional)	1"	1.5"
MAX.OP. PRESSURE	5kg/cm2	5kg/cm2	5kg/cm2
EJECTOR SUCTION @2kg/cm^3	170 LPH	450 LPH	750 LPH
EJECTOR RATIO	1:7	1:1	1:1

Available in Filter and Softener Configuration